



Technical specification bucket

JET 210 P

Jokey Euro Tainer Profi

dimensions


D1: 326,0 mm

D2: 311,0 mm

D3: 280,0 mm

H:* 331,0 mm

*Height without lid



handle types basic data volume to rim: 22,30 I tolerances weight: 570,0 g metal handle 46,0 g dimensions: +/- 1 mm weight group: Medium plastic handle 25,0 g volume/weight: +/- 5 % belt handle no handle body grip 3,0 g roller grips

 decoration
 Digital
 IML
 offset

 height:
 220,0 mm
 293,8 mm
 240,0 mm

 width:
 924,0 mm
 935,8 mm
 910,0 mm

 median breadth:
 924,0 mm
 924,0 mm

DET 325 P DET 325 PR DET 325 P FDET 325 P Lid standard shaker lid standard sealing lid stacking height two f 652,0 mm 652,0 mm 0,0 mm 671,0 mm each further: 320,0 mm 320,0 mm 0,0 mm 329,0 mm

logistic Max. compression for standard lid at 20°C on the lowest pail: 70,00 kg


pieces per pallet

Bucket 320 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 09.03.2015 rev. 2.0



Technical specification lid **DET 325 P**



dimensions

D1: 325,3 mm H: 14,4 mm

basic data displaced volume:: 1,00 I tolerances

> weight: 100,0 g dimensions: +/- 1 mm weight group: Medium volume/weight: +/- 5 %

decoration IML offset

JET2K 325 Pt

250,0 mm

Diameter 279,0 mm



JET 160 P



JET 180 P





JET 201 P

JET 210 P

JET2K 325 P




pieces per pallet

Lid 1920 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

Date: 09.03.2015 rev. 2.0

misc.

Bucket

logistic

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved



Technical specification lid **DET 325 PR**



dimensions

D1: 325,0 mm H: 16,0 mm

basic data displaced volume:: 1,20 I tolerances

> 120,0 g dimensions: +/- 1 mm weight: weight group: Medium volume/weight: +/- 5 %

decoration IML offset

JET 160 P

250,0 mm

Diameter 279,0 mm









Date: 09.03.2015 rev. 2.0

JET 210 P

logistic pieces per pallet


JET2K 325 P

960 Lid pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

Bucket

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid **DET 325 P**



dimensions

D1: 325,3 mm H: 14,4 mm

basic data displaced volume:: 1,00 I tolerances

> weight: 115,0 g dimensions: +/- 1 mm weight group: Heavy volume/weight: +/- 5 %

decoration IML offset

JET2K 325 Pt

Diameter 279,0 mm 250,0 mm

JET 160 P







JET 210 P

JET2K 325 P




pieces per pallet

Lid 960 pallet height 2,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material





QM / certificates

You can download our current certificates on www.jokey.com.

Date: 09.03.2015 rev. 2.0

misc.

Bucket

logistic

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved



Technical specification lid FDET 325 P



dimensions

D1: 325,0 mm H: 23,5 mm

basic data displaced volume:: 0,00 l tolerances

weight: 118,0 g dimensions: +/- 1 mm weight group: Medium volume/weight: +/- 5 %

decoration IML offset

Diameter 279,0 mm 250,0 mm

Bucket JET 160 P JET 180 P JET 200 P JET 201 P JET 210 P




logistic pieces per pallet

Lid 720 pallet height 1,20 m

layer quantities: 8

EUP (Europallet)

80 cm (31,5") x 120 cm (47,24")



material



QM / certificates

You can download our current certificates on www.jokey.com.

Date: 27.04.2016 rev. 2.1

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.